

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

5

1. (Original): A self positioning astragal seal, for use with an astragal having a bolt having a bolt retracted position and a bolt extended position, comprising:

a seal block having a catch and a hole,

said bolt slidably disposed through said hole,

10

said catch catching a portion of said bolt and holding said seal block in a

seal block retracted position when said bolt is in said bolt retracted

position and releasing said seal block when said bolt is in said bolt

extended position;

spring means forcing said seal block into a seal block extended position when

15

said seal block is released.

2. (Previously presented): The self positioning astragal seal according to claim 1, wherein said spring means comprises at least one compression spring.

20

3. (Previously presented): The self positioning astragal seal according to claim 1, wherein said seal block catch comprises a shoulder.

4. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said bolt portion comprises a shoulder.

5. (Previously presented): The self positioning astragal seal according to claim 3,
5 wherein said bolt portion comprises a shoulder,

said seal block shoulder catching said bolt shoulder and holding said seal
block in said seal block retracted position when said bolt is in said bolt
retracted position and releasing said seal block when said bolt is in said bolt
extended position;

10 6. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said seal block has an end seal.

7. (Previously presented): The self positioning astragal seal according to claim 1,
15 wherein said seal block has a face seal.

8. (Previously presented): The self positioning astragal seal according to claim 6,
wherein said seal block has a face seal.

20 9. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said self positioning astragal seal is installed on said astragal.

10. (Previously presented): The self positioning astragal seal according to claim 9,
wherein said astragal is affixed to a door having a door frame, said door frame
having a header and a sill.

5 11. (Previously presented): The self positioning astragal seal according to claim 10,
wherein said seal block has an end seal.

12. (Previously presented): The self positioning astragal seal according to claim 11,
wherein said end seal abuts said sill, when said seal block is in said seal block
10 extended position.

13. (Previously presented): The self positioning astragal seal according to claim 11,
wherein said end seal abuts said header, when said seal block is in said seal block
extended position.

15 14. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said astragal is affixed to a door having a door frame, said door frame
having a header and a sill, one said self positioning astragal is installed on said
astragal adjacent said sill and another said self positioning astragal is installed on
20 said astragal adjacent said header.

15. (Previously presented): The self positioning astragal seal according to claim 6,
wherein said astragal is affixed to a door having a door frame, said door frame
having a header and a sill, one said self positioning astragal is installed on said
astragal adjacent said sill and another said self positioning astragal is installed on
5 said astragal adjacent said header;

said end seal of said self positioning astragal seal adjacent said sill abuts said
sill, when said seal block is in said seal block extended position;

said end seal of said self positioning astragal seal adjacent said header abuts
said header, when said seal block is in said seal block extended position;

10

16. (Previously presented): The self positioning astragal seal according to claim 12,
wherein said seal block extended position is automatically adjusting

17. (Previously presented): The self positioning astragal seal according to claim 13,
15 wherein said seal block extended position is automatically adjusting

18. (Previously presented): The self positioning astragal seal according to claim 15,
wherein said seal block extended position is automatically adjusting

20 19. (Previously presented): The self positioning astragal seal according to claim 9,
wherein said astragal has a bolt retraction stop.

20. (Previously presented): The self positioning astragal seal according to claim 9,
wherein said astragal has a bolt extension stop.

21. (Previously presented): The self positioning astragal seal according to claim 9,
5 wherein said astragal has a seal block retraction stop and a seal block extension
stop;

said seal block retraction stop limiting the retracted extent of travel of said
seal block to said seal block retracted position;

said seal block extension stop limiting the released extent of travel of said

10 seal block when said seal block is released.

22. (Previously presented): The self positioning astragal seal according to claim 9,
wherein said seal block has a guide block adapted to guide said seal block
between said seal block retracted position and a seal block released position when
15 said seal block is released.

23. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said seal block has a guide block adapted to mount said self positioning
astragal seal to said astragal.

24. (Previously presented): The self positioning astragal seal according to claim 23,
wherein said guide block is adapted to guide said seal block between said seal

block retracted position and a seal block released position when said seal block is released.

25. (Previously presented): The self positioning astragal seal according to claim 23,
5 wherein said spring means comprises at least one compression spring abutting at least one portion of said seal block and abutting at least one portion of said astragal.

26. (Previously presented): The self positioning astragal seal according to claim 24,
10 wherein said spring means comprises at least one compression spring abutting at least one portion of said seal block and abutting at least one portion of said astragal.

27. (Previously presented): The self positioning astragal seal according to claim 1,
15 wherein said seal block has a guide block adapted to slidably maintain said seal block about said astragal and guide said seal block between said seal block retracted position and a seal block released position when said seal block is released.

20 28. (Currently amended): The self positioning astragal seal according to claim 1, wherein said astragal has an elongated guide and said seal block has a guide block adapted to slidably maintain said seal block about said elongated guide and guide

said seal block between said seal block retracted position and a seal block released position when said seal block is released.

29. (Previously presented): The self positioning astragal seal according to claim 28,
5 wherein said spring means comprises at least one compression spring abutting at least one portion of said seal block and abutting at least one portion of said elongated guide.

30. (Previously presented): The self positioning astragal seal according to claim 28,
10 wherein said elongated guide has a substantially centrally disposed longitudinal channel and opposing longitudinal side channels;
said bolt slidable within said substantially centrally disposed longitudinal channel.

15 31. (Previously presented): The self positioning astragal seal according to claim 30,
wherein said side channels have stops therein and said spring means comprises compression springs;
said compression springs abutting said seal block and abutting said stops.

20 32. (Currently amended): The self positioning astragal seal according to claim 31,
wherein said guide block has compression spring guide ~~holder~~ holders, said compression springs mounted about said compression spring holders.

33. (Previously presented): The self positioning astragal seal according to claim 28,
wherein said elongated guide has a seal block retraction stop and a seal block
extension stop;

5 said seal block retraction stop limiting the retracted extent of travel of said
seal block to said seal block retracted position;
said seal block extension stop limiting the released extent of travel of said
seal block when said seal block is released;

10 34. (Previously presented): The self positioning astragal seal according to claim 33,
wherein said guide block has a T shaped member adapted to guide said seal block
between said seal block retracted position and said seal block released position
when said seal block is released.

15 35. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said astragal has spring means and a latching mechanism having a latch;
said latching mechanism retracting said bolt into said bolt retracted position
and compressing said astragal spring means when said latch is retracted to a
latch retracted position;
20 said latching mechanism releasing said bolt and said astragal spring means
forcing said bolt into said bolt extended position and said latch into a latch
released position when said latch is released.

36. (Previously presented): The self positioning astragal seal according to claim 35,
wherein said astragal spring means comprises a compression spring.

5 37. (Previously presented): The self positioning astragal seal according to claim 9,
wherein said astragal has spring means and a latching mechanism having a latch;
said latching mechanism retracting said bolt into said bolt retracted position
and compressing said astragal spring means when said latch is retracted to a
latch retracted position;
10 said latching mechanism releasing said bolt and said astragal spring means
forcing said bolt into said bolt extended position and said latch into a latch
released position when said latch is released.

15 38. (Previously presented): The self positioning astragal seal according to claim 37,
wherein said astragal spring means comprises a compression spring.

39. (Previously presented): The self positioning astragal seal according to claim 28,
wherein said astragal has spring means and a latching mechanism having a latch;
said latching mechanism retracting said bolt into said bolt retracted position
20 and compressing said astragal spring means when said latch is retracted to a
latch retracted position;

said latching mechanism releasing said bolt and said astragal spring means forcing said bolt into said bolt extended position and said latch into a latch released position when said latch is released.

5 40. (Previously presented): The self positioning astragal seal according to claim 39, wherein said elongated guide has a substantially centrally disposed longitudinal channel and opposing longitudinal side channels;
 said bolt slidable within said substantially centrally disposed longitudinal channel.

10

41. (Previously presented): The self positioning astragal seal according to claim 40, wherein said side channels have stops therein and said self positioning astragal seal spring means comprises compression springs;
 said self positioning astragal seal compression springs abutting said seal
15 block and abutting said stops.

15

42. (Previously presented): The self positioning astragal seal according to claim 40, wherein said astragal spring means comprises a compression spring and said substantially centrally disposed longitudinal channel has said astragal
20 compression spring therein.

20

43. (Previously presented): The self positioning astragal seal according to claim 41,
wherein said astragal spring means comprises a compression spring and said
substantially centrally disposed longitudinal channel has said astragal
compression spring therein.

5

44. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said seal block is molded.

45. (Previously presented): The self positioning astragal seal according to claim 1,
wherein said seal block of an acetal material.

10

46. (Previously presented): The self positioning astragal seal according to claim 6,
wherein said end seal is of cellular material.

47. (Previously presented): The self positioning astragal seal according to claim 6,
wherein said end seal is of closed cell neoprene sponge material.

15

48. (Previously presented): The self positioning astragal seal according to claim 7,
wherein said face seal is of cellular material.

20

49. (Previously presented): The self positioning astragal seal according to claim 7,
wherein said face seal is of closed cell neoprene sponge material.

50. (Previously presented): The self positioning astragal seal according to claim 9, wherein said astragal is a locking astragal, which releasably locks said bolt into said bolt extended position.

5